



High Power
Bright



Mobile App
Smart Control



Step-less Dimming
Adjustable CCT



CRI 96+ High
Colorrendering Index



9 Scene
Lighting Effects

Falconeyes Bi-color Light **COB**

S80Bi & S200Bi

HIGH POWER, BRIGHT AND PORTABLE



DeSal Lite +



FalconEyes Official
WeChatAccount

FALCON EYES LTD.

Tel: 852-2363-2825

Fax: 852-2363-3856

Email: sales@falconeyeshk.com

Add:

Unit F1-215, 2/F,Phase 1,Hang Fung Building,2G
Hok Yuen Street, Hung Hom,Kowloon,Hong Kong.

Web: www.falconeyeshk.com

SHENZHEN FOTOTECH TECHNOLOGY CO.,LTD.

Mb: +86 136 8249 6801

QQ: 2850141642 / 2850141643

Add:

Unit 1038-1, Jiahui New Town, Jiahui Town 1/F Shopping
Center 8, Fuhua Road, Futian District, Shenzhen, China.

Web: www.fototech.com.cn

SHENZHEN SYNC IMAGE EQUIPMENT CO., LTD.

Mb: +86 137 6020 8711 / +86 158 1829 5140

QQ: 2850141648 / 3002473709

Add:

Room 1502, Building 1, No. 1 Jingdong Road, Fenggang
Town, Dongguan City, Guangdong Province, China

Web: www.falconeyes.com.cn

S80Bi / 80W



S80Bi Content list



S200Bi / 200W



S200Bi Content list



Specifications

Model No.	S80Bi	S200Bi
LEDs & Power	1pcs x (80W+80W)	1pcs x (200W+200W)
Output Wattage	80W	200W
Color Temperature	2500–9999K	2500–6500K
Operating Voltage	DC–16.8V 5.5A	DC–48V 5.2A
Compatibility	AC Adaptor	AC Adaptor
Dimming	0–100% Step-less dimming	0–100% Step-less dimming
Beam Angle	66° / 29° (+PD–LC80)	60° / 27° (+SR–18H)
Control Function	Switch+knob+key, APP	Switch+knob+key, APP
CRI	96+	96+
TLCI	97+	97+
Dimensions	Light: 235x145x95mm	Light: 205x180x135mm
Weight	Light: 0.9Kg AC Adaptor: 0.56Kg	Light: 1.5Kg
LUX(0.5m/1m/2m)	2500K: 7400lux / 1770lux / 457lux 5600K: 10800lux / 2560lux / 601lux – 2500K + PD–LC80: 118000lux / 14500lux / 2520lux 5600K + PD–LC80: 171000lux / 20800lux / 3700lux –	2500K: 31300lux / 7300lux / 1880lux 5600K: 39600lux / 9270lux / 2380lux 6500K: 38000lux / 8930lux / 2290lux 2500K + SR–18H: 167000lux / 29900lux / 6360lux 5600K + SR–18H: 200000lux / 38000lux / 8070lux 6500K + SR–18H: 200000lux / 36700lux / 7800lux

Variety of optional light modifiers



PDS-45 for S80Bi
DES-OB8 for S80Bi
PD-60 for S80Bi
PD-BW for S80Bi
PD-LC80 for S80Bi
P-BC01/02 for S80Bi
SOB70HC for S200Bi
SOB90HC for S200Bi
FTA-LB65 for S200Bi
FT-BHC for S200Bi
LPSA-BOF II for S80/200Bi
OSG-SQ for S80/200Bi